

# Nummernschlüssel: Kontakte TT53

*coding system: contacts TT53*

**TT53**   -

	<b>Draht</b> [mm <sup>2</sup> ] <i>wire</i> [inch <sup>2</sup> ]	<b>AWG</b> <i>AWG</i>	<b>max. Strom</b> <i>max. current</i>	<b>Ø A</b>	<b>Ø B</b>		<b>Kontakttyp</b> <i>contact type</i>		<b>Beschichtung</b> • <i>coating</i>		<b>Verpackung</b> <i>packaging</i>
16	0,75-1,5 <i>0.00116-0.00233</i>	20-16	10 A	1,8 <i>0.07</i>	2,55 <i>0.1</i>	C	Pin Crimpversion <i>pin crimpversion</i>	F*	Gold 0,2 µm <i>gold 0,2 µm</i>	0	Einzelkontakte 50 Stück <i>loose piece contacts 50 pcs.</i>
12*	2,5-4,0 <i>0.00387-0.00620</i>	14-12	20 A	2,8 <i>0.11</i>	3,7 <i>0.15</i>	D	Buchse Crimpversion <i>socket Crimpversion</i>	H	Gold 0,75µm <i>gold 0,75 µm</i>	1	Einzelkontakte 100 Stück <i>loose piece contacts 100 pcs.</i>
10	4,0-6,0 <i>0.00620-0.00930</i>	12-10	30 A	3,8 <i>0.15</i>	4,7 <i>0.19</i>	E	Pin Lötversion <i>pin brazing version</i>			2	Einzelkontakte 500 Stück <i>loose piece contacts 500 pcs.</i>
08*	6,0-10,0 <i>0.00930-0.01550</i>	10-08	50 A	4,8 <i>0.19</i>	5,6 <i>0.22</i>	F	Buchse Lötversion <i>socket brazing version</i>				

\* *Vorzugstypen*  
*preferred types*

• *weitere auf Anfrage*  
*others available on request*