



Reversibility  
next to the  
start button

Lightweight,  
well balanced  
'forward'  
pistol grip

Anti-slip  
insulating  
grip

*New*

**15C and 26C air screwdrivers  
with forward pistol grip and  
reversibility next to the start button**

- Torque range: from 0,4 to 12 Nm
- Automatic shut-off

**Fiam**<sup>®</sup>

PEOPLE AND SOLUTIONS

Type of screwdriver	Code	Grip	Tightening torque on soft joint		Idle speed	Starting system	Reversibility	Weight	Dimensions (mm)	Air consumption	Accessories	Noise level*	Vibrations	
			min.	max.										min.
Model		Type	Nm	in lb	rpm	Type	Type	kg	lb	ØxLxh	l/s	Drive	dBA	m/s <sup>2</sup>
15C2APA-2200-R	112514551		0,6÷2,2	5.31÷19.47	2.200			0,75	1.65	37x186x155	6	⊕ F 1/4"	71	< 2,5
15C3APA-1400-R	112514552		0,4÷3,5	3.54÷30.98	1.400			0,77	1.69	37x186x155	6	⊕ F 1/4"	71	< 2,5
15C4APA-950-R	112514553		0,4÷4,5	3.54÷39.83	950			0,77	1.69	37x186x155	6	⊕ F 1/4"	71	< 2,5
15C5APA-650-R	112514554		0,4÷5	3.54÷44.25	650			0,77	1.69	37x186x155	6	⊕ F 1/4"	71	< 2,5
26C4APA-2000-R	114814601		0,4÷4	3.54÷35.4	2.000			0,93	2.05	37x207x155	7	⊕ F 1/4"	73	< 2,5
26C5APA-1350-R	114814602		0,4÷5	3.54÷44.25	1.300			0,93	2.05	37x207x155	7	⊕ F 1/4"	73	< 2,5
26C8APA-1000-R	114814603		3,5÷8	30.98÷70.8	1.000			1,06	2.33	37x234x155	7	⊕ F 1/4"	73	< 2,5
26C10APA-800-R	114814609		3,5÷9,5	30.98÷84.08	800			1,06	2.33	37x234x155	7	⊕ F 1/4"	73	< 2,5
26C12APA-400-R	114814610		3,5÷12	30.98÷106.2	400			1,06	2.33	37x234x155	7	⊕ F 1/4"	73	< 2,5
15C2APA-2200-R-2CS	112514555		0,6÷2,2	5.31÷19.47	2.200			0,75	1.65	37x186x155	6	⊕ F 1/4"	71	< 2,5
15C3APA-1400-R-2CS	112514556		0,4÷3,5	3.54÷30.98	1.400			0,77	1.69	37x186x155	6	⊕ F 1/4"	71	< 2,5
15C4APA-950-R-2CS	112514557		0,4÷4,5	3.54÷39.83	950			0,77	1.69	37x186x155	6	⊕ F 1/4"	71	< 2,5
15C5APA-650-R-2CS	112514558		0,4÷5	3.54÷44.25	650			0,77	1.69	37x186x155	6	⊕ F 1/4"	71	< 2,5
26C4APA-2000-R-2CS	114814596		0,4÷4	3.54÷35.4	2.000			0,93	2.05	37x207x155	7	⊕ F 1/4"	73	< 2,5
26C5APA-1350-R-2CS	114814597		0,4÷5	3.54÷44.25	1.300			0,93	2.05	37x207x155	7	⊕ F 1/4"	73	< 2,5
26C8APA-1000-R-2CS	114814598		3,5÷8	30.98÷70.8	1.000			1,06	2.33	37x234x155	7	⊕ F 1/4"	73	< 2,5
26C10APA-800-R-2CS	114814599		3,5÷9,5	30.98÷ 84.08	800			1,06	2.33	37x234x155	7	⊕ F 1/4"	73	< 2,5
26C12APA-400-R-2CS	114814600		3,5÷12	30.98÷106.2	400			1,06	2.33	37x234x155	7	⊕ F 1/4"	73	< 2,5

Legend	Air inlet	Recommended hose bore
15 = Power of the motor in Watt/10 • C = Screwdriver 2 = Maximum tightening torque in Nm • A = Air shut-off system PA = 'Forward' pistol grip 2200 = Idle speed • R = Reversibility • 2CS = Double-signal pressure  <b>Reversibility:</b> all models are suitable for tightening and untightening operations <b>Push button</b>	15C ... 26C ... 1/4" gas	15C ...      Ø 5 mm 26C ...      Ø 8 mm

N.B.: Reversibility cursor can be positioned on the right or left of the start button

Clutch spring	Assembled on the tool - Grey colour Ø wire 3,2 mm cod. 595103202		Supplied - Black colour Ø wire 2,2 mm cod. 595102204	
	Model	Tightening torque on soft joint (Nm)	Tightening torque on soft joint (in lb)	Tightening torque on soft joint (Nm)
15C	0,8 ÷ at max torque	7.08 ÷ at max torque	From min torque ÷ 1,2	From min torque ÷ 10.62
26C4 ...	1 ÷ 4	8.85 ÷ 35.4	0,4 ÷ 1,3	3.54 ÷ 11.51
26C5 ...	1 ÷ 5	8.85 ÷ 44.25	0,4 ÷ 1,3	3.54 ÷ 11.51

- The figures shown are measured at a pressure of 6,3 bar (ISO 2787) the recommended operating pressure.
- Tightening torque values have been measured in accordance with ISO 5393 standard.
- Noise level has been measured in accordance with ISO 3744 and ISO 15744 standards. \*Additional factor: 3 dBA spread in method and production (ISO 15744).
- Vibrations level have been measured in accordance with ISO 8662-1 and ISO 8662-7 standards.
- Accessory drive: female hexagonal drive 1/4", 6,35 mm (ISO 1173).
- The code number must be used when ordering.

The data given in the table are indicative and can be changed without prior notice. The torque values are purely indicative and may be influenced by the softness of the type of joint, by the type and length of the screw, by the pressure and quantity of air supply, and by the type of accessory used. The values indicated for noise and vibration levels were obtained in the laboratory, performing tests that comply with the standards stated, but alone are not sufficient for calculating risks. Values measured in the single work places may be higher than those stated. The values of actual exposure and consequent risks are specific and depend on the operator's method of work, the type of work piece and the work place, as well as the operator's time of exposure and his physical conditions. Fiam cannot be held responsible for any consequences deriving from the use of the information in the table when evaluating risks in the work place over which Fiam has no control. For all further details, please apply to the Fiam Technical Consultancy Service.



**Fiam Utensili Pneumatici Spa**  
 Viale Crispi 123  
 36100 Vicenza - Italy  
 Tel. +39.0444.385000  
 Fax +39.0444.385002

customerservice@fiamairtools.com  
 www.fiamairtools.com

**Fiam France s.a.s.u.**  
 ZI Champ Dolin, 3 allée du Lazio  
 Bâtiment 3 - 3ème Etage  
 69800 Saint Priest - France  
 Tel. +33.4.78700150  
 Fax +33.4.78705403

serviceclient@fiamfrance.fr  
 www.fiamfrance.fr



Quality Management System Certificate



Environmental Management System Certificate